

# Goyen Diaphragm Valve-Kits

## MM IMMERSION VALVES MANIFOLD-MOUNT FOR FLAT (MM) & ROUND (MMR) TANKS



Dresser Nut vs Pipe Outlet MM Series

### GOYEN DIAPHRAGM VALVES

### DIAPHRAGM VALVE REPAIR KITS

Model	Port Size & Connection Type	Standard Temp. (-40°C to 82°C)	Low Temp. (-60°C to 82°C)	High Temp. (Viton) (-29°C to 232°C)
(R)CA25MM	1" IMMERSION VALVE (4-BOLT), FLAT TANK	<u>K2501 (M1183B)</u>	K2504	K2503 (M1887)
(R)CA40MM	1½" IMMERSION VALVE (6-BOLT), FLAT TANK	<u>K4502 (M1182)</u>	N/A	K4502 (M1156)
(R)CA40MMR	1½" IMMERSION VALVE (6-BOLT), ROUND TANK	<u>K4502</u>	N/A	K4503
(R)CA62MMR	2½" IMMERSION VALVE (8-BOLT), ROUND TANK	K7604	N/A	K7602
(R)CA76MM	3" IMMERSION VALVE (8-BOLT), FLAT TANK	K7600	N/A	K7601
(R)CA76MMR	3" IMMERSION VALVE (8-BOLT), ROUND TANK	K7600	N/A	K7601

